PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT

			WINDALL (FCI)
(51) International Patent Classification 6:	}	(11) International Publication Number:	WO 98/22690
E21B 17/08, 43/10, 43/08, F16L 13/14	Al		110 70/22070
		(43) International Publication Date:	28 May 1998 (28.05.98)
		·	

(21) International Application Number: PCT/EP97/060

(22) International Filing Date: 21 November 1997 (21.11.97)

(30) Priority Data: 96203272.8 22 November 1996 (22.11.96)

(34) Countries for which the regional or international application was filed: GB et al.

(71) Applicant (for all designated States except CA): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

(71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 - 4th Avenuc, S.W., Calgary, Alberta T2P 2H5 (CA).

(72) Inventor: LOHBECK, Wilhelmus, Christianus, Maria; Volmerlaan 6, NL-2288 GD Rijswijk (NL).

PCT/EP97/06671


(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TI, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TI, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BI, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: CONNECTOR FOR AN EXPANDABLE TUBING STRING



(57) Abstract

A connector for interconnecting a pair of adjacent sections (8 and 9) of an expandable tubing string comprises a plastically expandable sleeve (6) that is arranged co-axially around or inside the ends (7) of the interconnected tubing sections (8 and 9) and a series of circumferentially spaced mechanical fasteners (5), such as screws or rivets, for fastening the sleeve to each of said ends (7).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL.	Albenia	ES	Spain	LS	Lesotho	SI	Slovenia	
AM	Amenia	₽ĭ	Pinked	LT	Lithuania	SK	Slovakia	
AT	Austria	FR	Prance	w	Laxemboure	5N	Senegal	
AU	Ameralia	CA	Gabon	LV	Larvia	SZ	Swaziland	
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad	
BA	Bosnia and Herzegovina	CE	Georgia	MD	Republic of Moldova	TG	Togo	
88	Barbados	GH	Ghana	MG	Madaguscur	TJ	Tujikhtan	
38	Belgium	GN	Guinea	MX	The former Yugoslav	TM	Dakmenismo	
BY	Burkina Paso	GR	Greece		Republic of Macedonia	TR	Turkey	
BG	Dulgaria	HU	Hungary	ML	Mali	ıπ	Trinidad and Tobago	
BJ	Besin	(8	freland	MN	Mangalia	UA	Ukraine	
82	Brazil	IL.	Ternel	MR	Mauritania	UG		
BY	Belares	15	lorinal	MW	Malawi	US	Ugunda	
CA	Canada	n	haly	MX	Mexico	UZ	United States of America	
CP	Central African Republic	JP	Japan	NE	Niger	VN	Uzbekintas Viet Nara	
CC	Congo	KR	Kooya	NL	Netherlands			
CH	Switzerland	KG	Kyrgyzstan	NO	Norwey	YU	Yugastavia	
a	Côte d'Ivoire	KP	Democratic People's	NZ.		zw	Zimbabure	
CM	Cameroon	-	Republic of Korea	PL	New Zealand			
CX	China	1CR	Republic of Korea		Polend			
CU	Cuba	KZ.	Kazaketan	PT	Portugal			
æ	Creck Republic			RO	Romania			
DE.	Germany	ıc	Saint Lucia	RU	Russian Federation			
DK		u	Liechtenstein	SD	Sada			
EE	Dennurk Estonia	LK	Sri Lanka	SE	Sweden			
æ	CHOULE	LR	Liberia	8G	Singapore			
								-

10

15

20

25

CONNECTOR FOR AN EXPANDABLE TUBING STRING

The invention relates to a connector for use in connecting sections of an expandable tubing string, and in particular but not exclusively for use in the connection of sections of an expandable slotted tubing (EST) string as utilized in downhole applications in oil and gas production operations.

Expandable slotted tubings are known from International patent application No. PCT/EP 93/01460. This prior art reference discloses a slotted tube which may be expanded downhole by running an expansion mandrel through the tubing whereby the slots are expanded to diamond-shaped apertures.

When a tubing is expanded it is desirable that this can be accomplished by a substantially uniform expansion force, also at the locations where adjacent tubing sections are interconnected.

It is therefore an object of the present invention to provide a connector for an expandable tubing that can be expanded smoothly and made up easily without requiring welding operations.

The connector according to the invention thereto comprises a plastically expandable sleeve that is in use arranged co-axially relative to an end of each of the adjacent tubing sections, and means for fastening the sleeve to said ends.

Preferably the outer surface of an end of each of the adjacent tubing sections has been machined away to form an annular recess in which the sleeve is located.

10

15

20

25

30

Alternatively the inner surface of an end of each of the adjacent tubing sections has been machined away to form an annular recess in which the sleeve is located.

It is preferred that the thickness of the sleeve is substantially equal to the depth of the annular recess so that a flush-type connection is created.

It is furthermore preferred that the fastening means comprise a series of circumferentially spaced screws that pass through holes that are drilled through the sleeve and the adjacent wall of ends of the adjacent tubing sections. If desired the screws may be replaced by rivets or other mechanical fasteners.

The connector according to the invention is particularly attractive for interconnecting sections of an expandanble string of oil and/or gas well mentals that may be slotted. If the connector is used for interconnecting sections of an expandable slotted tubing string then the sleeve is provided with a series of staggered substantially longitudinal slots which are deformable into diamond-shaped apertures upon expansion of the sleeve.

Further aspects, details, objects and advantages of the connector according to the invention will become apparent from the accompanying claims, abstract, drawings and detailed description with reference to the drawings.

The invention will now be described in more detail with reference to the accompanying drawings, in which

Fig. 1 shows a schematic side view of a plastically expandable connector according to the invention which surrounds ends of adjacent expandable slotted tubing sections;

10

15

20

25

. 30

Fig. 2 shows a schematic longitudinal sectional view of a flush-type connector according to the invention which surrounds ends of adjacent expandable tubing sections; and

Fig. 3 shows a schematic longitudinal sectional view of a flush-type connector according to the invention which is surrounded by ends of adjacent expandable tubing sections.

Referring now to Fig. 1, there is shown a connector comprising a plastically deformable slotted sleeve 1 that co-axially surrounds ends of a pair of adjacent slotted tubing sections 2 and 3. The sleeve 1 and tubing sections are each provided with a series of staggered and partially overlapping slots 4 that deform to substantially diamond shaped apertures (not shown) upon expansion of the assembly by e.g. running an expansion mandrel (not shown) through the interior of the tubing sections 2 and 3.

One or more series of circumferentially spaced Allen-type or other locking screws 5 fasten the sleeve 1 to each of the tubing sections 2 and 3 such that the inner surface of the sleeve 1 engages the outer surface of the end of each tubing section 2 and 3 both before, during and after the expansion process. The screws 5 are located in nodes between slots 4.

Referring now to Fig. 2 there is shown a flush-type connector comprising a plastically deformable solid or slotted sleeve 6 that surrounds ends 7 of adjacent solid or slotted tubing sections 8 and 9, which ends 7 have been machined away to form an annular recess 10 in which the sleeve 6 is located. The thickness of the sleeve 6 substantially equals the depth of the recess 10 to form a flush-type connector.

10

15

20

- 4 -

The connector furthermore comprises a series of circumferentially spaced Allen-type or other locking screws 11 to fasten the sleeve 6 to each of the tubing sections 8 and 9 such that the inner surface of the sleeve 6 engages the outer surface of the ends 7 of the adjacent tubing sections 8 and 9 both before, during and after the expansion process.

Referring now to Figure 3 there is shown a flush-type connector comprising a plastically deformable solid or slotted sleeve 16 that is surrounded by ends 17 of adjacent solid or slotted tubing sections 18 and 19, respectively, which ends 17 have been machined away to form an annular recess 20 in which the sleeve 16 is located. The thickness of the sleeve substantially equals the depth of the recess 20 to form a flush-type connector that smoothly deforms plastically together with the ends of the tubing sections 18 and 19 during the expansion process.

The connector of Fig. 3 furthermore comprises a series of circumferentially spaced Allen-type locking screws 21 to fasten the sleeve 16 to each of the tubing sections 18 and 19 such that the outer surface of the sleeve 16 firmly engages the inner surface of the ends 17 of the adjacent tubing sections 8 and 9 both before, during and after the expansion process.

25

æ

25

CLAIMS


- 1. A connector for interconnecting adjacent sections of a tubing string, the connector comprising a sleeve that is in use arranged co-axially relative to an end of each of the adjacent tubing sections, and means for fastening the sleeve to said ends, characterized in that the sleeve is plastically expandable and is useable for interconnecting sections of an expandable tubing string.
- 2. The connector of claim 1, wherein the sleeve is

 designed for interconnecting sections of an expandable slotted tubing string and is provided with a series of staggered substantially longitudinal slots which are deformable into diamond-shaped apertures upon expansion of the sleeve.
- 3. The connector of claim 1, wherein the sleeve is designed for interconnecting sections of an expandable string of oil and/or gas well tubulars.
 - 4. The connector of claim 1, wherein the outer surface of an end of each of the adjacent tubing sections has been machined assure to fee
- been machined away to form an annular recess in which the sleeve is located.
 - 5. The connector of claim 1, wherein the inner surface of an end of each of the adjacent tubing sections has been machined away to form an annular recess in which the sleeve is located.
 - 6. The connector of claim 4 or 5, wherein the thickness of the sleeve is substantially equal to the depth of the annular recess.


application of property of the

Commence of the Commence of th

7. The connector of any preceding claim, wherein the fastening means comprise a series of circumferentially spaced screws that pass through holes that are drilled through the sleeve and the adjacent wall of ends of the adjacent tubing sections.







Inte Jonal Application N

			PCT/EP 97,	/06671
IPC 6	FICATION OF SUBJECT MATTER E21B17/08 E21B43/10 E21B43/	/08 F16L13/	14	
	o International Pelent Classification (IPC) or to both national classifi	cation and IPC		
	SEARCHED			
IPC 6	ocumentation searched (classification system followed by classifica E21B F16L	lion symbols)		
	on searched other than minimum documentation to the eident that			rched
Electronic d	ata base consulted during the international search (name of data b	ase and, where practical,	search terms used)	
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT			
Category *	Citation of document, with indication, where appropriate, of the re	levent passages		Relevant to claim No.
X	US 3 948 321 A (OWEN) 6 April 19 see column 5, line 13 - line 50 see column 7, line 37 - line 41	76		1,3-6
Υ.	, , , , , , , , , , , , , , , , , , , ,			2
Y	US 5 366 012 A (LOHBECK) 22 Nove cited in the application see the whole document	mber 1994		2 .
X	US 3 863 959 A (BLASCHKE) 4 Febr see abstract	1,3-7		
X .	DE 24 34 298 A (HERMANN VON RAUT INTERNATIONALE TIEFBOHR KG ITAG) January 1976 see page 4, line 9 – page 5, lin	1,3-7		
	page 4, The 9 - page 5, Th	e 0	ľ	Ì
	•	-/		
X Furth	er documents are listed in the continuation of box C.	X Palent family m	embers are fisted in	arnex.
* Special cat	egories of cited documents :	T lelecte		
"É" eartier d	nt defining the general state of the art which is not ared to be of particular relevance ocument but published on or after the international	invention	not in contict with the principle or the	ne application but any underlying the
"L" document which is classion	me ni which may throw doubts on priority claim(s) or a checi to establish the publication date of enother or other special reason (se specified)	" document of particul	ed novel or cannot b stap when the doc ar relevance: the cla	e considered to ament is taken alone limed invention
	nt referring to an oral disclosure, use, exhibition or	OCCUMENT IS COMPE	sed with one or more	offer such docu-
"P" docume	nt published prior to the international filing date but an the priority date claimed	in the art. "8" document member of		to a person skilled
Date of the s	ctual completion of theinternational search	Date of mailing of the		
24	March 1998	30/03/19	98	
Name and m	alling address of the ISA	Authorized officer		
	European Patent Ottica, P.B. 5818 Patentiaan 2 NL - 2290 HV Pajewijt. Tel. (+31-70) 340-2040, Tr. 31 651 epo nl. Fatt (+31-70) 340-3018	Sogno, N	1	

Form PCT/ISAQ10 (second after) (Adv 1997)

1

trits. .donal Application No PCT/EP 97/06671

TO CONTRACT OF TRACKS TO THE

Continu	NION) DOCUMENTS CONSIDERED TO BE RELEVANT	PCT/EP 97/06671
egory .		Relevant to claim No
	WO 95 25239 A (ATLAS COPCO GEOTECHNICAL DRILLING AB) 21 September 1995	1,3-5
	us 2 871 034 A (WILTSE) 27 January 1959 see column 1, line 59 - column 2, line 4	1,3,5,6
	GB 792 886 A (HUNTSINGER) 2 April 1958 see page 3, line 116 - line 124; figures 4,9,11	1,3,4,7
	US 3 585 803 A (BARDGETTE) 22 June 1971 see column 2, line 71 - column 3, line 1	1,3,4,7
	DE 90 13 606 U (BRM GMBH) 31 October 1991 see the whole document	1,3,7
	FR 1 565 562 A (RABUEL) 2 May 1969 see page 2, left-hand column, line 10 - right-hand column, line 4	1,3
	DE 41 33 802 C (HAWERKAMP) 22 October 1992 see the whole document	1,3
	WO 93 14284 A (WELAND AB) 22 July 1993 see page 4, line 4 - line 6 see page 5, line 6 - line 21	1,7
	DE 295 18 333 U (NOVOPRESS GMBH) 11 January 1996 see page 5, line 21 - line 26; figure 2	1
	EP 0 611 614 A (B & W FUEL COMPANY) 24 August 1994 see abstract	1
	DE 43 29 442 A (DEUTSCHE ALWA GMBH) 2 March 1995 see abstract	1
x	WO 96 37680 A (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ) 28 November 1996 see example 1	1-7
	see page 2, line 23 - line 28 see page 3, line 19 - line 25 see page 4, line 14 - line 17	
x	WO 96 37681 A (PETROLINE WIRELINE SERVICES LIMITED) 28 November 1996 see the whole document	1-7
	-/	
		*
. [

page 2 of 3

1

information on patent family members

PCT/FP 97/05671

West of the Sant Control

Patent document	Publication		/EP 97/06671
cited in search report	date	Patent lamily member(s)	Publication date
US 3948321 A	06-04-76	NONE	
US 5366012 A	22-11-94	AU 672008 B	19-09-96
		AU 4324593 A	04-01-94
		CA 2137565 A	23-12-93
		DE 69305852 D	12-12-96
		DE 69305852 T	22-05-97
		WO 9325800 A	23-12-93
		EP 0643795 A	22-03-95
		JP 7507611 T	24-08-95
		MD 960219 A	31-05-97
		NO 944746 A	03-02-95
		NZ 253125 A	27-02-96
US 3863959 A	04-02-75	CH 558872 A	14-02-75
		DE 2210980 A	23-08-73
		FR 2175229 A	19-10-73
		GB 1365657 A	04-09-74
		JP 48101614 A	21-12-73
DE 2434298 A	29-01-76	NONE	
HO 9525239 A	21-09-95	SE 503459 C	17-06-96
		AU 680753 B	07-08-97
		AU 2089095 A	03-10-95
		EP 0757768 A	12-02-97
		FI 963641 A	08-11-96
		NO 963833 A	25-10-96
		SE 9400867 A	16-09-95
JS 2871034 A	27-01-59	NONE	
68 792886 A	•	NONE	
JS 3585803 A	22-06-71	NONE	
E 9013606 U	31-10-91	NONE	
R 1565562 A	02-05-69	NONE	

PCT/EP 97/06671

alleberte dividence

(Continu	MION) DOCUMENTS CONSIDERED TO BE RELEVANT	PCT/EP 9	7,000/1
tegory *	Citation of document, with indication, where appropriate, of the relevant passages		Relevant to claim No.
(,P	WO 97 41377 A (B.O.KENDLE ENGINEERINGLIMITED) 6 November 1997 see page 13, line 6 - line 9; figure 15 see page 7, line 19 - line 21; figure 6 see page 10, line 1 - line 3		1,3-6
-			
·			

page 3 of 3

information on patent family members

PCT/EP 97/06671

SUMMERS A LIBERT

Patent docume	201	Publication		PCT/EP 97/06671
cited in search re		date	Patent tamity member(s)	Publication date
DE 4133802	. C	22-10-92	NONE	
WO 9314284	A	22-07-93	SE 500185 (C 02-05-94
			AT 154964	
			DE 69220677 (
			DE 69220677	T 15-01-98
			EP 0624219 /	
			FI 943449 A	
			NO 942659 /	
			SE 9200179 A	22-07-93
DE 2951833	3 U	11-01-96	NONE	
EP 611614	A	24-08-94	WO 9419125 A	01-09-94
DE 4329442	A	02-03-95	NONE	
WO 9637680	A	28-11-96	AU 5826596 A	11-12-96
		•	AU 7349396 A	11-12-96
			EP 0828918 A	
			EP 0824628 A	25-02-98
			WO 9637681 A	28-11-96
			NO 975350 A	16-01-98
WO 9637681	A	28-11-96	AU 5826596 A	11-12-96
			AU 7349396 A	11-12-96
		-	WO: 9637680 A	28-11-96
			EP 0828918 A	18-03-98
			EP 0824628 A	25-02-98
			NO 975350 A	16-01-98
WO 9741377	Α	06-11-97	AU 2647497 A	19-11-97

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record.

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.